



L2800 Compact Tractors

Competitive Comparison								
MODEL		Kubota L2800-1		John Deere 3005	John Deere 3032E	New Holland T1510		
		Gear 2WD/4WD	HST 4WD	Gear	HST 4WD	Gear 2WD/4WD	HST 4WD	
Engine	Engine gross power	HP(kw)	30.0 (22.4)		27 (17.9)	31.4 (23.4)	30.0 (22.4)	
	PTO power	HP(kw)	25.0 (18.6)	23.5 (17.5)	24 (17.6)	25 (18.6)	25.5 (19.0)	24.0 (17.9)
	No. of cylinders		3		3	3	3	
	Total displacement	c u.in.(cm3)	91.5 (1499)		81.2 (1331)	97.6 (1599)	91.3 (1496.1)	
	Rated revolution		2800		2700	2500	2600	
	Fuel tank capacity	gal.(l)	9.0 (34.0)		6.3 (23.8)	6.4 (24.2)	7.1 (27)	
	Air cleaner		Single Element (Dual Optional)		Dry Type Air Cleaner w/ Safety Element	Dry Type Air Cleaner w/ Safety Element	Dual Element	
Drive train	Transmission		Sliding Gear & Constant Mesh	HST	Gear	HST 4WD	Gear	HST
	No. of traveling speeds		8F/4R	3-Range	8F/2R	2-Range	9F/3R	3-Range
	Max. traveling speed	mph(km/h)	13.7 (22.0)	14.7 (23.6)	12.7 (20.5)	12.4 (20)	12.1 (19.5)	13.6 (21.9)
	Brake		Multiple Wet, Disc		Dry Shoe	Wet, Disc	Wet, Disc	
	PTO clutch		Transmission driven w/ overrunning clutch	Continuous Live	Continuous Live	Independent	Transmission Driven/ Live (Optional)	Continuous Live
Tires	Farm	Front	5-15/11.2 - 24		2WD: 5.9 -15 4WD: 7 -14	7 - 14	7.4 x 14	
		Rear	7-16/11.2 - 24		2wd: 11.2 - 24 4wd: 11.2 - 24	11.2-24	11.2 x 24	
	Turf	Front	23 x 8.50 - 12		25 x 8.50 - 14 4PR	27 x 8.5 - 15	24 x 8.50 - 14	
		Rear	13.6 - 16		13.6 - 16 4PR	41 x 14.0 - 20	13.6 x 16	
	R4	Front	N/A	27 x 8.50 - 15	25 x 8.50 - 14 6PR	25 x 8.5 - 14	25 x 8.50 - 14	
		Rear	N/A	15 - 19.5	15.0 - 19.5 6PR	15.00 - 19.5	15 x 19.5	
Hydraulic System	Pump capacity	gpm(l/min)	10.5 (39.7)		9.4 (36.5)	9.3 (35.2)	6.2 (23.3)	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	1435 (651)		815 (370)	1356 (615)	1635 lb. (743)	
	Power steering		Integral Type Power Steering		Standard	Hydrostatic Power Steering	Standard (Hydrostatic)	
Dimensions	Wheelbase	in.(mm)	63.3 (1610)		61 (1550)	60 (1525)	63.0 (1600)	
	Overall Length (w/ 3pt.)	in.(mm)	119.1 (3025)	115.0 (2920)	111 (2821)	111 (2819)	111.4 (2830)	
	Overall Height (w/ ROPS)	in.(mm)	85.0 (2160)		82 (2083)	82.3 (2090)	82.3 (2090)	
	Overall width (min. tread)	in.(mm)	51.4 (1305)		54 (1362)	56.5 (1435)	46.1 (1170)	
	Min. ground clearance	in.(mm)	13.6 (345)	13.4 (340)	N/P	13.0 (330)	12.2 (310)	
	Min. turning radius w/ brake	ft.(m)	7.9 (2.4) / 8.2 (2.5)	8.2(2.5)	7 (2.1)	N/P	8.0 (2.5)	
	Weight (w/ROPS)	lbs.(kg)	2359 (1070) / 2536 (1150)		2600 (1180)	2WD: 1929 (875) 4WD: 2105 (955)	2175 (987)	2385 (1082)

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.