



THE 680GC



680GC A WHOLE DIFFERENT ANIMAL

Built to meet the operational and flexibility demands of the general construction user, the 680GC stands alone in terms of reliability and value. Packed with innovations and loaded with dependability, the 680GC is the perfect saw for the less frequent user. The distinctive black powerhead houses specially designed carburetion and ignition systems that work together to ensure easy starting, cooler operation, and dependable performance at just about any elevation. Improved airflow design keeps the engine much cooler, extending its life. Available with 12-inch (30 cm) and 14-inch (35 cm) guidebars and the entire line of MAX series diamond chain.

680GC PRODUCT SPECIFICATIONS	
WEIGHT	21 lbs 9.6 kg (without bar and chain)
BAR LENGTH	Up to 14 in (35 cm)
HORSEPOWER	5 hp (3.7 KW) @ 9500 rpm
ENGINE TYPE	2-stroke, single cylinder air cooled
DISPLACEMENT	4.7 cu. inch (77 cc)
POWERHEAD DIMENSIONS	18 in (45 cm) length 11.5 in (29 cm) height 10 in (25 cm) width
NOISE LEVEL	100 dB @ 3 ft (1 m)
VIBRATION LEVEL	10.5 meters/second ² (front handle)
WATER SUPPLY	Minimum 20 psi (1.5 bar)
FUEL MIX RATIO	25:1 (4%)
FUEL CAPACITY	0.23 gal (0.88 liter), 15-18 minutes run time per tank

SAW SELECTION

In addition to cutting depth and power requirements, estimated frequency of use is important when selecting a saw. Use the chart below to determine the right saw for your cutting needs.

