



Husqvarna DM 230

New, handheld drill motor with attractive design and functional ergonomics. Soft rear section and a larger contact area mean that it sits better against your body. The machine is modular, and therefore easy to maintain and repair.



OVERLOAD PROTECTION

The Elgard™ feature available on several of our drill motors means that if the motor runs at too high a load for a long period, it will start to pulsate. If the load is not reduced the motor will shut off, to prevent overheating. Elgard™ significantly increases the machine's service life.



SOFT REAR SECTION

The DM 230 sits comfortable against your body due to the soft rear section and a larger contact area.



HANDLE WITH INTEGRATED WATER HOSE

The handle has an integrated water hose, which together with the electric cable run parallel conveniently from the machine.



THREE GEARS

The DM 230 is equipped with three gears.

Features Husqvarna DM 230

- Functional ergonomics make the Husqvarna drill motors easy and convenient to operate.
- Thanks to a three-way valve integrated in the front of the drill motor, you can easily change between dry and wet drilling.
- Several of our products has the Smart Start® feature which means that by pressing the SmartStart button speed is reduced by half, making it easier to start drilling.
- Equipped with Elgard™ which uses pulsation to indicate when the machine is overloaded. This extends product life.
- When making a starter hole or cutting through reinforcement speed can be reduced by half using SmartStart.
- Pressing the SmartStart™ button reduces start speed by 50 %. Useful also when cutting through rebar.
- Three-speed water-cooled gearbox for optimal drilling performance and longer service intervals.
- The plastic housing makes it more durable against drops and daily wear.

TECHNICAL SPECIFICATION	
Voltage	230/110V
Amperage	8/15 A
Power	1850 W
Phases	1
Output RPM	700/1700/3600 rpm
Output RPM at full load	580/1400/2900 rpm
Speeds	3
Water coupling	G 1/4"
Spindle speed full load	580/1400/2900 rpm
Rated output, W	1850/0 W
Rated current, A	8/15 A
Max drill bit diameter, handheld	3 in (80 mm)
Max drill bit diameter, stand	6 in (150 mm)
Mounting collar	2.4 in (60 mm)
Spindle thread, outer	1 1/4" 7 UNC
Spindle thread, inner	G 1/2" or 5/8" 11 UNC
UNC water coupling	G 1/4"
Weight	15.41 bs (7 kg)
Sound pressure	90 dB(A)
Sound level	94 dB(A)
Hand arm vibration (Aeq)	2,5 m/s ²
Power rating	1100 W

