



SURFACE PREPARATION STRIPPERS



FCS16 RIP-R-STRIPPER®

The FCS Series RIP-R-STRIPPERS® have revolutionized the industry with their innovative design and operational features. Quickly remove VCT tiles, rubber-backed carpeting and sheet type coverings from wood and concrete surfaces. Welded, unitized frame. Adjustable operator handle folds for transport. Direct-drive, random orbit action; 14 lbs external weight. Includes 1 each, part number FCS16-1100, 4" x 6" straight blade and 1 each, part number FCS16-1300, 3" x 10" straight blade.

FEATURES

- 16 inch maximum cutting blade width.
- Back-Saver™ Blade Control System.
- Magnetic-type ON/OFF switch.
- 37 foot extension cord w/GFI.

SPECIFICATIONS

Operating Environments	Non-hazardous type locations
Electric Motor	.75HP, 115VAC, 60HZ, 15 amperes
Nominal Oscillations	1725/minute
Frame	Unitized, welded steel plate
Bearings	Ball-type
Drive System	Direct
Extension Cord	12-3, SJTW x 37 ft (11 m) L, w/GFI
Dimensions	Width: 14-1/2 inch (368 mm). Width (at operator handle): 23 inch (584 mm). Height (at operator handle extension): 42 inch (1067 mm). Length (handle folded): 24 inch (610 mm). Length (at operator configuration): 34 inch (864 mm).
Weight	132 lbs (59 kg), less blade

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF13021201