STANDARD FEA	TURES							
2017 MODELS	RS-9	U-12	U-14	U-19	LS-20	U-23	U-24	U-24GN
Maximum Payload	1,950 lbs.	4,500 lbs.	10,000 lbs.	10,000 lbs.	4,500 lbs.	9,500 lbs.	15,000 lbs.	15,000 lbs.
Axle Rating	3,500 lbs.	$1 \times 7,000$ lbs.	2 x 7,000 lbs.	$2 \times 7,000$ lbs.	2 x 3,500 lbs.	2 x 7,000 lbs.	$3 \times 7,000$ lbs.	$3 \times 7,000$ lbs.
Trailer Weight	1,050	2,100	3,600	4,000	2,500	4,500	5,400	6,000
Overall Width	94"	82"	102"	102"	102"	102"	102"	102"
Overall Length	14'	15'7"	19'6"	23'8"	24' 9"	27' 4"	28' 4"	33'8"
Loading Surface Area	72" x 9'	60" x 10'10"	80" x 14'	80" x 18'	80" x 19'	80" x 22'	80" x 23'	80" x 23'
Deck Surface	Treated Pine	Hardwood	Hardwood					
Lifting Device	Hydraulic w/ Elec. Assist	Hydraulic w/ Eec. Assist						
Suspension	Single Axle Torsion	Single Axle Torsion	Twin Axle Torsion	Twin Axle Torsion	Twin Axle Torsion	Twin Axle Torsion	Tri-Axle Torsion	Tri-Axle Torsion
Electric Brakes	Optional	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Wheel Size	14"	16"	16"	16"	14"	16"	16"	16"
Hitch Size	2"	2 - 5/16"	2 - 5/16"	2 - 5/16"	2"	2 - 5/16"	Pintle	Gooseneck
Systems & Storage Box	Standard	Standard						
Lighting	LED	LED						
Welded D-Rings	N/A	4	6	6	N/A	6	6	6
Tie Down Chain Key Slots	=	(4) 2/Side-Frt & Rear	(4) 2/Side-Frt & Rear	(4) 2/Side-Frt & Rear	-	(4) 2/Side-Frt & Rear	(4) 2/Side-Frt & Rear	(4) 2/Side-Frt & Rear
Battery	Group 31	Group 31						
Stake Bed Pockets	Standard	Standard						
Safety Lock	N/A	Standard	Standard	Standard	N/A	Standard	Standard	Standard
Warranty	1 Year	1 Year						

FEATURES & BENEFITS

NO RAMP ADVANTAGES

- Eliminate injuries caused by heavy ramps such as pulled back muscles, smashed feet, and severed fingers that lead to worker comp claims or law suits.
- Save time & money as loading/unloading can be done with-or-without tow vehicle being attached.
- Avoid equipment damage as low approach angle protects equipment from damage caused by falling off ramps during loading and unloading.

LOW APPROACH ANGLE

- Ability to load any low clearance equipment quickly and safely due to low approach angle.
- Applications: Skid Steers, Scissor Lifts, Fork Lifts, Construction, Farming, Industrial Cleaning Equipment, plus so much more...

LOCKING MECHANISM

 For assured safety of load, in case of accidental hydraulic line damage.

LED RUBBER MOUNTED LIGHTING

 Better visibility for safety, and low voltage draw for battery life.

ADJUSTABLE COUPLER

Allows for any truck in the fleet to do the towing.

AUXILIARY RECEIVER

Used for winch mount and other needs.

EASY ACCESS GREASE ZERKS

 Deck side grease zerks for axle pins, and fender hinges.

FACTORY MOLDED WIRE HARNESS

 All connections use molded components for long life operation

BUILT-IN THEFT PREVENTION

Frees up time and reduces theft exposure Lower trailer, lock it, and leave it!

NO JACK NEEDED FOR TIRE CHANGES

Reduces time with added safety. Break lug nuts loose, apply blocks under each rear corner of trailer, and lower unit to raise tires off the ground.

TORSION AXLE

Superior ride and long life

STAKE BED POCKETS WITH RUB RAIL

 Provides additional tie down locations, framing-or-racking opportunity, and added main frame strength.

15' EXTENSION CORD CONTROL MODULE

 Allows for activation of trailer at the systems box, or up to 15' away.

COURTESY LIGHTING

 Deck side and systems box courtesy lighting on all U-Series Models.

OPTIONS AVAILABLE FOR ALL MODELS

- Custom Colors
- Military CARC Coating
- Wireless Remote Key Fob
- Spare Tire
- Spare Tire Rack
- Aluminum Custom Wheels
- Mobile D-Rings
- Trailer Deck Mounted Receiver
- Pintel Hitch
- Winch Plate
- Winch
- Solar Trickle Charger
- 10amp On-Board Battery Charger
- Hardwood Decking
- Diamond Plate Steel Decking
- Electric/Hydraulic Jack Stand
- Drum Surge Brakes