

Husqvarna PG 280 SF.

Use the QR-tag
to check out
more about
the PG 280 SF.



The ideal grinder for rental customers who need to grind concrete, mastics, paints, etc. It's small and easy to maneuver, yet strong enough to get the job done.

Applications.

- Perfect for grinding adhesive residue, paint and spackle on medium-sized concrete areas.
- Efficiently grinds due to high rpm levels and a wide range of discs available for various applications.

Benefits.

- The dust guard and vacuum port are designed to create efficient suction of dust and therefore create an almost dustless environment.
- Easy and convenient to use, with ergonomically designed handlebar and low noise levels.
- Large range of diamond tooling available for a wide range of grinding applications.



Ergonomically designed handlebar.



Single grinding plate with multiple diamond tool distribution positions.

Product specifications.


	PG 280 SF	PG 280 SF	E
Item no.	966987420	966987415	

Technical specifications.

Power, hp (kW)	2 (1.5)	3 (2.2)
Voltage, V	110-120	220-240
Rated current, amps	18	18
Power supply	1-phase	1-phase
Grinding width, in (mm)	11 (280)	11 (280)
Grinding disc, in (mm)	11 (280)	11 (280)
Grinding pressure total, lbs (kg)	55 (25)	55 (25)
Power per grinding disc, hp (kW)	2 (1.5)	3 (2.2)
Grinding disc speed, rpm	1,160	1,720
Dimensions, in (mm) (LxWxH)	47 x 16 x 39 (1,200 x 410 x 1,000)	
Weight, lbs (kg)	154 (70)	154 (70)
Recommended generator size	6 kW	7-1/2 kW

Accessories.

		P
A	Redi Lock™ diamond disc holder	522677301
B	Rubber damper	510213101
	Rubber skirt	574272001
	Resin pad adapter	574653701
	Pigtail adapter (115V, 30amp model)	581488201
	PG 280 carbide holder	581276802



Redi Lock™ diamond disc holder.



Rubber damper.