



COLD PLANER SERIES II

For Skid Steer Loaders



The **FFC Cold Planer**, by Paladin, can be used to make full depth utility cuts, mill frost heaves around manholes, restore proper drainage to pavement, add texture to pavement for skid resistance, and much more.



- Scarifies concrete and planes sidewalks and street joints
- 2 sizes available for standard flow skid steers; 6 sizes available for high-flow skid steers
- Side shifts 24" left or right to cut next to curbs and obstacles
- Solid drum pushes milled material to the back, preventing remilling
- V style pic pattern for efficient milling

COLD PLANER SERIES II

- Optimized bit pattern provides a faster cut by maximizing the horsepower per bit
- In-cab fingertip controls operate sideshift, tilt, and cutting depth on high-flow models
- High-flow models feature planetary gearbox drive for increased torque and durability.

Specifications Standard Flow		
Model	LAF5412	LAF5413
PSI Range	2200-3400 lbs	2200- 3400 lbs
Weight (approx)	1135 lbs	1225 lbs
Cutting Width	12"	16"
Cutting Depth	0-5.00"	0-5.00"
Tilt	±15°	±15°
Sideshift	24"	24"
Pic Qty.	36	44
GPM Range	13-25	16-25

Specifications High Flow						
Model	LAF5416	LAF5418	LAF5420	LAF5424	LAF5430	LAF5436
PSI Range	2200-5000 lbs	2200-5000 lbs	2200-5000 lbs	2200-5000 lbs	2200-5000 lbs	2200-5000 lbs
Weight (approx)	1510 lbs	1560 lbs	1610 lbs	1690 lbs	1855 lbs	2015 lbs
Cutting Width	16"	18"	20"	24"	30"	36"
Cutting Depth	0-6.00"	0-6.00"	0-6.00"	0-6.00"	0-6.00"	0-6.00"
Tilt	±15°	±15°	±15°	±15°	±12.5°	±10°
Sideshift	24"	24"	24"	24"	24"	24"
Pic Qty.	48	52	56	64	76	88
GPM Range	24-45	26-45	26-45	28-45	28-45	31-45

Cold Planer Series II Carrier Specifications:

lift capacities < 10,000 lbs
operating weight < 20,000 lbs

When work needs to get done you need to be able to depend on your equipment. Our Cold Planers are designed for maximum reliability, durability, and productivity.