

Commercial ZTrak™ Zero-Turn Mowers

E Series | M Series | R Series | R Series Diesel



Keep Mowing.

ZTrak™ Mowers

Contents

ZTrak Overview.....	2-3
ZTrak 7Iron™/Mulch On Demand™	4-5
ZTrak E Series	6-7
ZTrak M Series	8-9
ZTrak R Series	10-11
ZTrak R Series Diesel	12-13
ZTrak Attachments and Accessories.....	14-15
Commercial Mowing Support.....	16-19
ZTrak Specifications	20-24

We're in the business of supporting your business.



Z925M Flex Fuel EFI



Z970R



Z930M



Z915E



Z997R Diesel

Feel at home with our family of ZTrak mowers.



It's all about you. And you. And you.

Our ZTrak 900 Series Zero-Turn Mowers were designed with our commercial mowing customers in mind. And since you all have different needs, we came up with different ways to help you meet them.

It starts with the E Series, a mower that perfectly balances performance and value. It gives you the essential features – including excellent weight distribution, professional-grade seats and a mow-all-day fuel tank – at a price that's essentially ideal.

With the M Series, we focused on those of you who have a lot to look after – and a big need for efficiency – with Electronic Fuel Injection (EFI) and Flex Fuel options, Mulch On Demand decks, and Dump From Seat (DFS) Material Collection System (MCS) capability, and diagnostic capability.

The R Series was created for contractors who demand the best and want the ultimate feature set. You can see the attention to detail in everything from the Comfort & Convenience controls and Hydraulic Cross-Porting transmission to the Brake-N-Go foot pedal start. Not to mention the 3-year, 1,500-hour warranty.[^]

Ready to put the Power of 3 to work for you? Read on.

Key Features

E SERIES	M SERIES	R SERIES	R SERIES DIESEL
<ul style="list-style-type: none"> Commercial-grade components Large rear tyres Professional-grade seats Warranty: 36 months or 1,200 hours, whichever comes first; first 24 months, no hour limitation[^] 	<ul style="list-style-type: none"> 7Iron PRO decks with optional Mulch On Demand (MOD) Flat Free front tyres Tuff Torq® heavy-duty integrated transmission Warranty: 36 months or 1,200 hours, whichever comes first; first 24 months, no hour limitation[^] 	<ul style="list-style-type: none"> Cross-Porting Hydraulic Transmission Comfort & Convenience Package Brake-N-Go starting Warranty: 36 months or 1,500 hours, whichever comes first; first 24 months, no hour limitation[^] 	<ul style="list-style-type: none"> Powerful 27.9 kW diesel engine 7Iron PRO decks with optional MOD Shaft-driven mower decks with heavy-duty gear box Warranty: 36 months or 1,500 hours, whichever comes first; first 24 months, no hour limitation[^]

E SERIES

Z915E



M SERIES

Z920M
Z925M Flex Fuel EFI
Z930M
Z930M EFI
Z950M
Z960M



R SERIES

Z930R
Z950R
Z970R



R SERIES DIESEL

Z997R



ZTrak™ M Series

Z920M Z930M Z950M Z960M
Z925M Flex Fuel EFI Z930M EFI

Efficiency in action.
Value in every cut.





When you've got a lot to manage, you don't have a lot of time for babysitting fussy, hard-to-maintain mowers. You probably don't have a lot of money to throw at them either. You need equipment that's rugged and dependable; zero-turn mowers that are efficient out in the field and easy to manage back in the garage.

Sounds to us like you need to meet the M Series.


The Z920M, Z925M, Z930M, Z950M, and Z960M hit the sweet spot where value-driven performance and day-in, day-out driving durability come together. They deliver all the power you need, the effortless Mulch On Demand™ you want – and build quality that ensures years of reliable operation at every turn.

Features include:


- Engine options
 - 17.5 kW (23.5 hp*), 19 kW (25.5 hp*), 20.1 kW (27 hp*) or 23.1 kW (31 hp) petrol engine
 - 18.6 kW (25 hp*) or 19.8 kW (26.5 hp*) Electronic Fuel Injection (EFI)
 - 18.6 kW (25 hp*) Flex Fuel
- Seat options
 - Base seat
 - Base seat + Isolation package
 - 3-way adjustable suspension seat
- 7Iron™ PRO decks available in 121.9 cm (48 in.), 137.2 cm (54 in.), 152.4 cm (60 in.) and 182.9 cm (72 in.) widths
- Mulch On Demand available in 121.9 cm (48 in.), 137.2 cm (54 in.) and 152.4 cm (60 in.) widths
- 16.1 km/h maximum ground speed
- Brake-N-Go hand brake
- Warranty: 36 months/1,200 hrs, no hour limit within first 24 months^



Flat free front tyres keep things rolling right along.



Transmission with heavy-duty unitised pump and wheel motor improves cooling and access.



Expanded height-of-cut range is easy to adjust and lock in place.



Electronic Fuel Injection gives you the option of turning your commercial-grade mower into a fuel-sipping dynamo. The closed-loop system allows just the right amount of fuel and spark to the engine, at just the right time – not only delivering fuel savings, but optimising power, performance and efficiency across all mowing conditions as well. Choose the Z925M Flex Fuel model, and you get the added benefit of mowers that can run on any blend up to E85.

ZTrak™ Specifications

Engine	
Certified Horsepower	
Engine Model	
Displacement	
Cylinders	
Oil Filter	
Lubrication	
Cooling	
Air Cleaner	
Fuel System	
Fuel Type	
Fuel Tank Capacity	
Electrical System	
Charge System	
Battery Voltage	
Hour Meter	
Operator Presence Starting System	
Drive Train	
Hydraulic Pumps	
Wheel Motors	
Hydraulic Capacity	
Travel Speed Forward	
Travel Speed Reverse	
PTO	
Type	
Drive	
Brakes	
Park Brake	
Park Brake Actuation	
Mower Decks	
Available Widths / Type	
Deck construction	
Deck thickness	
Height-of-Cut Range / Increment	
Blades	
Tip Speed	
Number	
Wheels and Tyres	
Drive (Rear) Tyres	
Caster Wheel Type	
Caster Wheel Size	
Dimensions	
Overall Length	
Overall Width	
Height	
Weight (with Fluids)	
Warranty *	
Duration	
Type	

E SERIES

Z915E

18.6 kW (25 hp*) @ 3,600 RPM
CV742
747 cc
Two
Full flow, replaceable
Full pressure
Air
Heavy-duty canister type with safety element
Petrol
43.5 L
15 amp
12 Volt
Standard, digital
Brake-N-Go (hand)
Tuff Torq® heavy-duty integrated piston pump
Tuff Torq heavy-duty integrated piston wheel motor
5.58 L
0-16.1 km/h
0-7.2 km/h
Electro-magnetic (271 Nm / 200 lb. ft.)
V-belt
Internal wet disk integrated in the transmisson
Hand brake
121.9 cm (48 in.), 137.2 cm (54 in.) and 152.4 cm (60 in.)
7Iron™ II (One-piece stamped steel with reinforcements)
7 gauge 4.5 mm (0.177 in.)
25.4 - 139.7 mm (1 to 5.5 in.) / 6.4 mm (0.25 in.)
Approximately 18,000 fpm
Three
24x9.5-12 Turf (48 in.), 24x12-12 Turf (54 in., 60 in.)
Pneumatic
13x5-6
213.4 cm (84 in.)
157.5 cm (62 in.), 172.7 cm (68 in.) and 188 cm (74 in.) with chute down
185.4 cm (73 in.) with ROPS up; 119.4 cm (47 in.) with ROPS down
499 to 534 kg (1,100 to 1,178 lb.)
36 months or 1,200 hours, whichever comes first, no hour limitation for the first 24 months
Single Source Commercial

M SERIES

Z920M

17.5 kW (23.5 hp*) @ 3,600 RPM
FX730V
726 cc
Two
Full flow, replaceable
Full pressure
Air
Heavy-duty canister type with safety element
Petrol
43.5 L
20 amp
12 Volt
Standard, digital
Brake-N-Go (hand)
Tuff Torq heavy-duty integrated piston pump
Tuff Torq heavy-duty integrated piston wheel motor
5.58 L
0-16.1 km/h
0-7.2 km/h
Electro-magnetic (271 Nm / 200 lb. ft.)
V-belt
Internal wet disk integrated in the transmisson
Hand brake
121.9 cm (48 in.), 121.9 cm (48 in.) MOD, 137.2 cm (54 in.) and 152.4 cm (60 in.)
7Iron PRO (One-piece stamped steel with reinforcements)
7 gauge 4.5 mm (0.177 in.)
25.4 - 139.7 mm (1 to 5.5 in.) / 6.4 mm (0.25 in.)
Approximately 18,000 fpm
Three
24x9.5-12 Turf (48 in.), 24x12-12 Turf (54 in., 60 in.)
Flat free
13x6.5-6
213.4 cm (84 in.)
157.5 cm (62 in.), 172.7 cm (68 in.) and 188 cm (74 in.) with chute down
185.4 cm. (73 in.) with ROPS up; 119.4 cm (47 in.) with ROPS down
553 to 582 kg (1,220 to 1,283 lb.)
36 months or 1,200 hours, whichever comes first, no hour limitation for the first 24 months
Single Source Commercial

Specifications and design subject to change without notice.

Z925M Flex Fuel EFI

18.6 kW (25 hp*) @ 3,600 RPM
ECV740
747 cc
Two
Full flow, replaceable
Full pressure
Air
Heavy-duty canister type with safety element
Petrol
43.5 L
20 amp
12 Volt
Standard, digital
Brake-N-Go (hand)
Tuff Torq heavy-duty integrated piston pump
Tuff Torq heavy-duty integrated piston wheel motor
5.58 L
0-16.1 km/h
0-7.2 km/h
Electro-magnetic (305 Nm / 225 lb. ft.)
V-belt
Internal wet disk integrated in the transmisson
Hand brake
137.2 cm (54 in.), 137.2 cm (54 in.) MOD and 152.4 cm (60 in.)
7Iron PRO (One-piece stamped steel with reinforcements)
7-gauge 4.5 mm (0.177 in.)
25.4 - 139.7 mm (1 to 5.5 in.) / 6.4 mm (0.25 in.)
Approximately 18,000 fpm
Three
24x12-12 Turf
Flat Free
13x6.5-6
213.4 cm (84 in.)
172.7 cm (68 in.) and 188 cm (74 in.) with chute down
185.4 cm (73 in.) with ROPS up; 119.4 cm (47 in.) with ROPS down
539 to 590 kg (1,188 to 1,300 lb.)
36 months or 1,200 hours, whichever comes first, no hour limitation for the first 24 months
Single Source Commercial

Z930M / Z930M EFI

19 kW (25.5 hp*) / 19.8 kW (26.5 hp*) @ 3,600 RPM
F801V / ECV749
852 cc / 747 cc
Two
Full flow, replaceable
Full pressure
Air
Heavy-duty canister type with safety element
Petrol
43.5 L
20 amp
12 Volt
Standard, digital
Brake-N-Go (hand)
Tuff Torq heavy-duty integrated piston pump
Tuff Torq heavy-duty integrated piston wheel motor
5.58 L
0-16.1 km/h
0-7.2 km/h
Electro-magnetic (305 Nm / 225 lb. ft.)
V-belt
Internal wet disk integrated in the transmisson
Hand brake
137.2 cm (54 in.), 137.2 cm (54 in.) MOD / 152.4 cm (60 in.) and 152.4 cm (60 in.) MOD
7Iron PRO (One-piece stamped steel with reinforcements)
7-gauge 4.5 mm (0.177 in.)
25.4 - 139.7 mm (1 to 5.5 in.) / 6.4 mm (0.25 in.)
Approximately 18,000 fpm
Three
24x12-12 Turf
Flat Free
13x6.5-6
213.4 cm (84 in.)
188 cm (74 in.) and 218.4 cm (86 in.) with chute down
185.4 cm (73 in.) with ROPS up; 119.4 cm (47 in.) with ROPS down
578 to 619 kg (1,275 to 1,365 lb.)
36 months or 1,200 hours, whichever comes first, no hour limitation for the first 24 months
Single Source Commercial

Z950M

20.1 kW (27 hp*) @ 3,600 RPM
FX850V
852 cc
Two
Full flow, replaceable
Full pressure
Air
Heavy-duty canister type with safety element
Petrol
43.5 L
20 amp
12 Volt
Standard, digital
Brake-N-Go (hand)
Tuff Torq heavy-duty integrated piston pump
Tuff Torq heavy-duty integrated piston wheel motor
5.58 L
0-16.1 km/h
0-7.2 km/h
Electro-magnetic (305 Nm / 225 lb. ft.)
V-belt
Internal wet disk integrated in the transmisson
Hand brake
152.4 cm (60 in.), 152.4 cm (60 in.) MOD and 182.9 cm (72 in.)
7Iron PRO (One-piece stamped steel with reinforcements)
7-gauge 4.5 mm (0.177 in.)
25.4 - 139.7 mm (1 to 5.5 in.) / 6.4 mm (0.25 in.)
Approximately 18,000 fpm
Three
24x12-12 Turf
Flat Free
13x6.5-6
213.4 cm (84 in.)
188 cm (74 in.) and 218.4 cm (86 in.) with chute down
185.4 cm (73 in.) with ROPS up; 119.4 cm (47 in.) with ROPS down
578 to 619 kg (1,275 to 1,365 lb.)
36 months or 1,200 hours, whichever comes first, no hour limitation for the first 24 months
Single Source Commercial

Z960M

23.1 kW (31 hp) @ 3,600 RPM
FX921V
999 cc
Two
Full flow, replaceable
Full pressure
Air
Heavy-duty canister type with safety element
Petrol
43.5 L
20 amp
12 Volt
Standard, digital
Brake-N-Go (hand)
Tuff Torq heavy-duty integrated piston pump
Tuff Torq heavy-duty integrated piston wheel motor
5.58 L
0-16.1 km/h
0-7.2 km/h
Electro-magnetic (305 Nm / 225 lb. ft.)
V-belt
Internal wet disk integrated in the transmisson
Hand brake
152.4 cm (60 in.), 152.4 cm (60 in.) MOD and 182.9 cm (72 in.)
7Iron PRO (One-piece stamped steel with reinforcements)
7-gauge 4.5 mm (0.177 in.)
25.4 - 139.7 mm (1 to 5.5 in.) / 6.4 mm (0.25 in.)
Approximately 18,000 fpm
Three
24x12-12 Turf
Flat Free
13x6.5-6
213.4 cm (84 in.)
188 cm (74 in.) and 218.4 cm (86 in.) with chute down
185.4 cm (73 in.) with ROPS up; 119.4 cm (47 in.) with ROPS down
568 to 608 kg (1,252 to 1,340 lb.)
36 months or 1,200 hours, whichever comes first, no hour limitation for the first 24 months
Single Source Commercial

Specifications and design subject to change without notice.



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all countries or regions. In some countries, products and accessories may require modifications or additions to ensure compliance with the local regulations of those countries. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification and design of all products described in this literature without notice. John Deere's green and yellow colour scheme, the leaping deer symbol, and JOHN DEERE are trademarks of Deere & Company. All photography and illustrations contained herein are copyrighted assets of Deere & Company.

*The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information.

†Hour and/or usage limitations apply and vary by model. See the limited warranty for new John Deere Commercial equipment at dealer for details.

DSTA54975AU (02-17)



JOHN DEERE

JohnDeere.com.au | JohnDeere.co.nz