

# PROCAT™ 6000



MODEL NUMBER	9996001	9996003	9996002	9996004
<b>ENGINE</b>				
Model	Kaw FX730V	Kaw FX730V	Kaw FX801V	Kaw FX801V
Displacement (cc)	726	726	852	852
Fuel Capacity (gal)	15	15	15	15
Air Filter	Canister Air Filter			
<b>ELECTRICAL</b>				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	225	225	225	225
<b>DECK</b>				
Mower Deck	AirFX™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width (in)	52	52	61	61
Adjustable Anti-Scalp Rollers	6	6	6	6
Cutting Height (in)	1–5.5	1–5.5	1–5.5	1–5.5
Blade Tip Speed	18586 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
<b>FRAME</b>				
Front & Rear	Welded 0.25 in, 7-gauge Steel; 1.5 x 2.5 in Steel Tubing			
Machine Length (in)	83	83	83	83
Machine Weight—Wet (lb)	1427	1371	1477	1421
<b>TRANSMISSION</b>				
Type	HG Pumps with HG Wheel Motors	HG ZT-4400 Hydrostatic Transaxles	HG Pumps with HG Wheel Motors	HG ZT-4400 Hydrostatic Transaxles
Pump Displacement (cc)	12	12	12	12
Oil Capacity (qt)	9	4.5 each	9	4.5 each
Forward Speed (mph)	0–11	0–12	0–11	0–12
Reverse Speed (mph)	0–4	0–4	0–4	0–4
<b>WHEELS</b>				
Drive Wheel Size	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
<b>SEAT</b>				
Description	High-Back, Full-Mechanical Suspension Seat			
Fore-Aft Adjustment	Seat Slide Lever			
<b>WARRANTY</b>	6-year / 2,750 hour MOW WITH CONFIDENCE™ limited warranty			

**Parts & Accessories:** Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, BOSS-Vac™ Pro 12-bushel, BOSS-Vac™ 8-bushel, ZT Hitch Kit, No-Flat Caster Wheel Options, 61-inch Wide Track Kit, Magnetic Light Kit—12V, Striping Kit (48", 52", 61"), Light Kit—Footplate, Operator-Controlled Discharge Chute



## FIERCELY INDEPENDENT.

BOBCATTURF.COM