



Husqvarna K 760 Cutn-Break

Our Cut-n-Break method is the natural choice when you need to cut deep without overcutting at the corners. The K 760 Cut-n-Break enables you to cut as deep as 16" from one side. The two high-speed blades make a core in the saw cut, which can then easily be broken off using the accompanying breaking tool. This way you easily work your way through the material, at a very low diamond tool and maintenance cost. Delivered with twin blades and a breaking tool.

Engine	
Output power	5 hp
Cylinder displacement	4.48 cu.inch
Electrode gap	0.02 in
Dimensions	
Product size width	9.69 in
Product size height	17.56 in
Weight	21.2 lbs
Vibrations	
Vibrations left/front handle	1.9 m/s ²
Vibrations right/rear handle	2.8 m/s ²

Cutting depth, max	16 in
Blade diameter, max	9 in
Peripheral speed, max	16000 fpm
Hydraulics	
Sound and noise	
Sound power level, guaranteed (LWA)	115 dB(A)
Sound pressure level at operators ear	101 dB(A)
Certifications	
Cert machine dir. 2006/42/EC Decl. No.	EURO TEST CERTIFICATE SEC/ 13/2369

Cutting equipment

Features for K 760 Cut-n-Break

Cost-efficient cutting method



With the unique cut-n-break method you can work your way through the material step-by step at a low tool cost.

High performing blades included

Twin blades, with a very stable core and cutting performance are delivered with the machine.

Exceptional cutting depth



The long body and double cutting blades allow you to make cuts up to 16" deep.

Optimized engine performance



Optimized engine performance through efficient cylinder design, digital ignition system and X-Torq® engine technology.

Recommended tools for K 760 Cut-n-Break



Concrete hard	$\bullet \bullet \bullet$	$\bullet \bullet \bigcirc$	
Concrete medium	• 0 0	• • •	
Concrete soft		• • •	• 0 0
Green concrete			• • 0
Natural stone	• • •		