



**WACKER
NEUSON**
all it takes!

4-stroke rammer BS60-4As, 280 mm ramming shoe

5200018232

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Rammers](#) >> [4 Stroke Rammer](#) >> **4-stroke rammer BS60-4As, 280 mm ramming shoe**

4-stroke rammer BS60-4As, 280 mm ramming shoe

Material number 5200018232

Four-stroke vibratory rammer with 280 mm ramming shoe for soil compaction, Honda GX engine



Product details

- Long shoe stroke, high percussion rate and high impact energy with fast advance travel achieve high performance results
- Low oil protection: Unit will not start if sensor detects no oil or low oil, protecting the engine
- Simple operation with only one lever for acceleration and shutoff
- Powered by Honda GX 100 engine and designed for the compaction of cohesive, mixed and granular soils in confined areas
- Unique four-stage air filtration system provides longer life and improved durability

Comes with

- Vibratory rammer
- Operator's Manual

Technical specifications

4-stroke rammer BS60-4As, 280 mm ramming shoe

SHIPPING AND STORAGE

Shipping weight	80,00 kg
-----------------	----------

MECHANICAL - OUTPUT DETAILS

Number of blows	690 1/min
-----------------	-----------

MECHANICAL DETAILS

Length	673 mm
Width	343 mm
Height	965 mm
Weight	72,00 kg
Length Ramming Shoe	336 mm
Width Ramming Shoe	280 mm
Stroke at tamper	78 mm

ENVIRONMENT DATA

Sound level LpA	91,0 dB(A)
Sound level LpA (Standard)	EN 500-4
Sound power LWA, measured	104,0 dB(A)
Sound power LWA, guaranteed	108,0 dB(A)
Sound power LWA (Standard)	2000/14/EG
HAV summation (average value)	6,5 m/s2

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

ENGINE

Engine type	Gasoline engine
Effective power	null, 2,4 kW
Nominal Engine speed	4.200 1/min, null
Cylinder	1
Cylinder capacity	98 cm3
Engine Manufacturer	Honda
Cooling	air cooling
Tank capacity	3,00 l
Exhaust-gas limit	EPA Phase2 & EU2002/88/EC, EPA3
Kraftstofftyp	Gasoline
Air cleaner	dry air filter
Engine operating mode	four-stroke
Fuel consumption	0,90 L/Std
Fuel management	Carburettor
Oil specification	SAE 10W-30
Oil filling max.	0,40 l
Oil filling min.	0,40 l
Operating power	2,4 kW
Operating Engine speed	4.200 1/min
Electrode distance	0,60 - 0,70 mm
Starter type	Recoil starter

Custom Attributes

Model serie	BS60-4
-------------	--------

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2022 Wacker Neuson SE