

## ELECTRIC SERIES SCISSOR LIFTS

# 0608SE(1930SE)/0608ME(1932ME)

Compliance with ISO/CE/ANSI/CSA/AS/EAC standards

### PRODUCT HIGHLIGHTS

#### Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

#### Reduced maintenance costs

- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts

#### Reliable performance

- Bumper rail protection



Standard features		
Maintenance-free battery	Automatic braking system	Drive at full height
Proportional control	Emergency lowering system	Forklift pocket and lifting eyes
Bumper rail	Emergency stop at both platform and ground controls	Electrophoresis paint technology
2WSx2WD	Fault diagnosis system	Foldable guardrail
Non-marking tyres	Tilt protection	Overload sensing system
Integrated hand shield	Automatic pothole guard	
Optional features		
Overhead anti-collision device	Headlight	RCBO
AC power to platform	Foot switch	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

[SINOBOOM.COM](http://SINOBOOM.COM) | [SALES@SINOBOOM.COM](mailto:SALES@SINOBOOM.COM)

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

## ELECTRIC SERIES SCISSOR LIFTS

**0608SE(1930SE)/0608ME(1932ME)**

Compliance with ISO/CE/ANSI/CSA/AS/EAC standards

Model	0608SE/0608ME(1930SE/1932ME)
Dimensions	
Max Working Height	7.8m(25'7")
A Max Platform Height	5.8m(19')
B Max Horizontal Extension	0.9m(3')
C Length-Stowed	1.8m(5'11")
D Width-Stowed	0608SE 0.79m(2'7") / 0608ME 0.81m(2'8")
E Height-stowed (Rail Folded)	1.88m(6'2")
E Height-stowed (Rail Unfolded)	2.14m(7')
F Wheelbase	1.33m(4'4")
Ground Clearance(Pothole Guard Stowed)	75mm(3")
Ground Clearance(Pothole Guard Deployed)	24mm(0.95")
Platform Dimensions(LxWxH)	1.64mx0.76mx1.1m(5'5"x2'6"x3'7")
Performance	
Platform Allowable Occupants(Indoor/Outdoor)	0608SE(2persons/-), 0608ME(2persons/1 person)
Platform Capacity	230kg(507lbs)
Drive Speed-Stowed	4km/h(2.5mph)
Drive Speed-Raised	0.8km/h(0.5mph)
Elevation Time(Unloaded)	15s~20s
Descent Time(Unloaded)	25s~30s
Gradeability	25%
Turning Radius(Inside/Outside)	0/1.49m(0/4'11")
Tilt Rating(Front to Back/Side to Side)	3°/1.5°
Tyre Size/Type	323x100mm(12.7x4")/solid
Power	
Batteries	6Vx4/225Ah
Power Source	24V DC
Drive Mode	Motor, front-wheel
Charger Input	100~240V AC
Charger Output	30A
Hydraulic Tank Capacity	7L(1.54gal(UK)/ 1.85gal(US))
Weight	
Weight	1,575kg(3,473lbs)
Standards Compliance	
ISO/CE/ANSI/CSA/AS/EAC	

