



**WACKER  
NEUSON**  
*all it takes!*

## WP1550A

5100062423

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Plates](#) >> [Single direction Vibratory Plates](#) >> **WP1550A**

### WP1550A

Material number 5100062423

Single direction vibratory plate for soil compaction



### Product details

- Sturdy protective frame for engine and water tank
- Low-maintenance design for low TCO
- Optimally shaped base plate

### Comes with

- Device
- Operating manual

## Technical specifications

### WP1550A

<b>OPERATING FLUIDS</b>	Imperial	Metric
Tank capacity	1,0 gal US	3,60 l

  

<b>ENGINE</b>	Imperial	Metric
Fuel management	Carburettor	Carburettor
Inclined position max.	20,0 °	20,0 °
Engine operating mode	four-stroke	four-stroke
Operating Engine speed	3.520 1/min	3.520 1/min
Fuel consumption	0,2 GPH US	0,80 L/Std
Standard (Power max.)	SAE J1349	SAE J1349
Standard (Effective power)	ISO 3046 IFN	ISO 3046 IFN
Nominal Engine speed	3.600 1/min, 3.600 1/min	3.600 1/min, 3.600 1/min
Electrode distance	0,028 - 0,032 "	0,70 - 0,80 mm
Oil filling max.	0,2 gal US	0,60 l
Effective power	4,2 hp, 4,8 hp	3,1 kW, 3,6 kW
Battery capacity (nom. value)	0 Ah	0 Ah
Air cleaner	Cyclone air filter	Cyclone air filter
Power rating max.	4,8 hp	3,6 kW
Cooling	air cooling	air cooling
Exhaust-gas limit	EPA4/08	EPA4/08
Oil specification	SAE 10W-30	SAE 10W-30
Starter battery Voltage	0 V	0 V
Engine speed (Power max.)	3.600 1/min	3.600 1/min
Starter type	Recoil starter	Recoil starter
Operating power	3,9 hp	2,9 kW
Oil filling min.	0,2 gal US	0,60 l
Engine type	Gasoline engine	Gasoline engine
Cylinder	1	1

Engine Manufacturer	Honda	Honda
Standard (Operating power)	ISO 3046 IFN	ISO 3046 IFN
Cylinder capacity	9,9 Inch <sup>3</sup>	163 cm <sup>3</sup>
Spark plug(s)	NGK BP-6 ES	NGK BP-6 ES
Kraftstofftyp	Gasoline	Gasoline
Oil volume incl. filter change	0,2 gal US	0,60 l

<b>MECHANICAL - OUTPUT DETAILS</b>	Imperial	Metric
Vibrations	5.880 1/min	5.880 1/min
Forward running	1,6 fps	29,00 m/min
Transmission	FKK-KR	FKK-KR
Gradeability	36,4 %	36,4 %
Centrifugal force	3.372 lbf	15,000 kN
Vibrations (Hz)	98,0 Hz	98,0 Hz
Area capacity	9.364,7 ft <sup>2</sup> /h	870 m <sup>2</sup> /h

<b>ENVIRONMENT DATA</b>	Imperial	Metric
Operating temperature range	5 - 104 °F	-15 - 40 °C
Sound level LpA (Standard)	EN 500-4	EN 500-4
Sound power LWA, guaranteed	108,0 dB(A)	108,0 dB(A)
Storage temperature range	5 - 104 °F	-15 - 40 °C
HAV summation (average value)	19,4 ft/s <sup>2</sup>	5,9 m/s <sup>2</sup>
Uncertainty in measurement HAV	1,6 ft/s <sup>2</sup>	0,5 m/s <sup>2</sup>
HAV summation (Standard)	EN 500-4	EN 500-4
Sound level LpA	93,0 dB(A)	93,0 dB(A)
Sound power LWA (Standard)	EN 500-4	EN 500-4
Sound power LWA, measured	107,0 dB(A)	107,0 dB(A)

<b>MECHANICAL DETAILS</b>	Imperial	Metric
Lenght Drawbar in op. pos.	34,1 "	865 mm
Operating weight	198,4 lb	90,0 kg

Ground clearance	21,7 "	551 mm
Height	37,9 "	963 mm
Width	19,7 "	500 mm

<b>Custom Attributes</b>	Imperial	Metric
Model serie	WP	WP

**Please Note**

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2023 Wacker Neuson SE